



Specifications

Cellular WAN Interfaces	Single LTE Modem	Weight	120g
Redundant SIM Slot	Yes	Operating Temperature	32° – 104°F / 0° – 40°C
Downlink/Uplink Datarate	CAT-12: 600 Mbps/150 Mbps CAT-6: 300Mbps/50Mbps	Humidity	15% – 95% (non-condensing)
Antenna Connectors	2x SMA Cellular, 1x SMA GPS	Warranty	1-Year Limited Warranty
Power Input	5V USB-C	Certifications	FCC, CE, IC
Power Consumption	TBA	Package Content	MAX Adapter, 2x 2dBi 4G LTE Antennas, USB-C power cable
Dimensions	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm		

Ordering information

Product Code	Carrier/Category	5G Bands	LTE Bands
MAX-ADP-5GH-T	Global/5G	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79 5G (SA) Sub 6Ghz: n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71